

A–A





material
safety part: heat-treated steel
hub: high-tensile strength aluminum
clamping ring: heat-treated steel
elastomer spider: polyurethan – 98 Shore A
screws: ISO 4762 / 12.9

Technical Data:
setting range: 130 – 330 Nm
torsional stiffness: 3,6 Nm/arcmin
max. axial shaft displacement: ± 1,0 mm
max. lateral shaft displacement: 0,12 mm
mass: approx. 4,6 kg
moment of inertia: 0,006 kgm²
ΦD1 min/max: 19 / 40 mm
ΦD2 min/max: 32 / 44 mm
temperature range: -30°C up to +90°C

		Änderung				Werkstoffbezeichnung	Werkstoffnummer	Maßstab
						-	-	1:1
						Rohteil-/Vorteilnummer	Gewicht	
						-	- kg	
		gepr.	03.07.20	Wu		safety coupling SKB-ES 330		
Passung	Abmaß	gez.	14.04.16	Be		Benennung		
DIN ISO 13715	DIN ISO 2768-mK		Datum	Name		Format A3	MB - 143 17850-e	
-0,4 +0,8	0,5 ... 6 ± 0,1 6 ... 30 ± 0,2 30 ... 120 ± 0,3 120 ... 315 ± 0,5 315 ...1000 ± 0,8				JAKOB Antriebstechnik D-63839-Kleinwallstadt	Artikelnummer		
						Ersatz für -	ersetzt durch -	

Eigentumsrechte, Urheberrechte und Vervielfältigungsverbot beachten, siehe auch DIN 34.