

A–A





Technical Data:

setting range:	60 – 150 Nm
torsional stiffness:	1,2 Nm/arcmin
max. axial shaft displacement:	± 1,0 mm
max. lateral shaft displacement:	0,1 mm
mass:	approx. 2,1 kg
moment of inertia:	1,6 10^{-3} kgm²
ϕD1 min/max:	14 / 36 mm
ϕD2 min/max:	24 / 35 mm
temperature range:	-30°C up to +90°C

material

safety part:	heat-treated steel
hub:	high-tensile strength aluminum
clamping ring:	heat-treated steel
elastomer spider:	polyurethan – 98 Shore A
screws:	ISO 4762 / 12.9

		Änderung				Werkstoffbezeichnung: -	Werkstoffnummer: -	Maßstab: 1:1
						Rohteil-/Vorteilnummer: -	Gewicht: - kg	
		gepr.	03.07.20	Wu		safety coupling SKB-ES 150	
Passung	Abmaß	gez.	14.04.16	Be			
DIN ISO 13715 -0,4 +0,8	DIN ISO 2768-mK: 0,5 ... 6 ±0,1; 6 ... 30 ±0,2; 30 ... 120 ±0,3; 120 ... 315 ±0,5; 315 ...1000 ±0,8	Datum	Name		Benennung		
		JAKOB Antriebstechnik D-63839-Kleinwallstadt			Format A3	Artikelnummer: MB - 143 17848-e	
					Ersatz für: -	ersetzt durch: -	

Eigentumsrechte, Urheberrechte und Vervielfältigungsverbot beachten, siehe auch DIN 34.