



Technical Data:

setting range: 6 – 12 Nm
 torsional stiffness: 0,25 Nm/arcmin
 max. axial shaft displacement: $\pm 0,5$ mm
 max. lateral shaft displacement: 0,1 mm
 mass: approx. 0,4 kg
 moment of inertia: $0,11 \cdot 10^{-3} \text{ kgm}^2$
 $\Phi D1$ min/max: 8 / 20 mm
 $\Phi D2$ min/max: 5 / 11,5 mm
 temperature range: -30°C up to $+90^\circ\text{C}$

material

safety part: heat-treated steel
 clamping hub: high-tensile strength aluminium
 elastomer spider: polyurethane – 98 Shore A
 screws: ISO 4762 / 12.9

		Änderung				Werkstoffbezeichnung	Werkstoffnummer	Maßstab
						-	-	
						Rohteil-/Vorteilnummer	Gewicht	3:2
						-	- kg	
		gepr.	31.07.20	Wu	safety coupling SKY - EK 12			
Passung	Abmaß	gez.	17.04.20	Be				
DIN ISO 13715	DIN ISO 2768-mK	Datum	Name	Benennung	Format A4 MB - 145 23848 -e			
	0,5 ... 6 ± 0,1 6 ... 30 ± 0,2 30 ... 120 ± 0,3 120 ... 315 ± 0,5 315 ... 1000 ± 0,8	 D-63839-Kleinwallstadt		Artikelnummer				
		Ersatz für	-	ersetzt durch	-			

JAKOB
Antriebstechnik

D-63839-Kleinwallstadt