



Technical Data:

setting range: 22 - 45 Nm
 torsional stiffness: 9 Nm/arcmin
 max. axial shaft displacement: $\pm 0,5$ mm
 max. lateral shaft displacement: 0,2 mm
 mass: approx. 0,9 kg
 moment of inertia: $0,45 \cdot 10^{-3} \text{ kgm}^2$
 $\phi D1$ min/max: 16 / 32 mm
 $\phi D2$ min/max: 10 / 17 mm
 temperature range: -30°C up to $+200^\circ\text{C}$

material

safety part: heat-treated steel
 clamping hub: high-tensile strength aluminium
 bellows: stainless steel
 screws: ISO 4762 / 12.9

Änderung					Werkstoffbezeichnung	Werkstoffnummer	Maßstab
					-	-	1:1
					Rohteil-/Vorteilnummer	Gewicht	
					-	- kg	
		gepr.	31.07.20	Wu	safety coupling SKY - KP 45		
		gez.	14.07.20	Be			
Passung	Abmaß	DIN ISO 13715	DIN ISO 2768-mK	Datum	Name	Benennung	Format A4
		-0,4	0,5 ... 6 $\pm 0,1$			Artikelnummer	MB - 145 23839 - e
		+0,8	6 ... 30 $\pm 0,2$			Ersatz für	-
			30 ... 120 $\pm 0,3$			ersetzt durch	-
			120 ... 315 $\pm 0,5$				
			315 ... 1000 $\pm 0,8$				
JAKOB Antriebstechnik				D-63839-Kleinwallstadt			