





* reduced tightening torque
Ts=50 Nm for bore diameter D > ϕ35

Technical Data:

setting range:	130 – 330 Nm
torsional stiffness:	28 Nm/arcmin
max. axial shaft displacement:	± 0,8 mm
max. lateral shaft displacement:	0,2 mm
mass:	approx. 3,5 kg
moment of inertia:	0,005 kgm²
ϕD1 min/max:	32 / 43 mm
ϕD2 min/max:	22 / 35 mm
temperature range:	–30°C up to +200°C

material
safety part: heat-treated steel
clamping hub: high-tensile strength aluminium
bellows: stainless steel
screws: ISO 4762 / 12.9
ISO 4017 / 10.9

		Änderung			Werkstoffbezeichnung: -	Werkstoffnummer: -	Maßstab: 1:1
					Rohteil-/Vorteilnummer: -	Gewicht: - kg	
		gepr.	10.07.20	Wu	safety coupling SKY - KP 330		
Passung	Abmaß	gez.	24.05.17	Be	Benennung		
DIN ISO 13715 -0,4 +0,8	DIN ISO 2768-mK: 0,5 ... 6 ±0,1; 6 ... 30 ±0,2; 30 ... 120 ±0,3; 120 ... 315 ±0,5; 315 ...1000 ±0,8	Datum	Name		Format A3	MB - 145 22238 - e	
		JAKOB Antriebstechnik D-63839-Kleinwallstadt			Artikelnummer		
					Ersatz für -	ersetzt durch -	

Eigentumsrechte, Urheberrechte und Vervielfältigungsverbot beachten, siehe auch DIN 34.