



#### technical data:

nominal torque: 30 Nm  
 maximum torque: 60 Nm  
 torsional stiffness: 6 Nm/arcmin  
 moment of inertia:  $0,18 \times 10^{-3} \text{ kgm}^2$   
 max. axial shaft displacement:  $\pm 0,8 \text{ mm}$   
 max. lateral shaft displacement: 0,25 mm  
 axial spring rate: 50 N/mm  
 lateral spring rate: 190 N/mm  
 temperature range:  $-40^\circ$  up to  $+350^\circ\text{C}$   
 maximum speed: 14.000 rpm  
 $D1/2\text{min}/\text{max} = \phi 10 / \phi 28 \text{ mm}$

#### material:

bellows: stainless steel 1.4571 / A4  
 hubs: stainless steel 1.4301 / A2  
 clamping screws: ISO 4762 - 12.9

Änderung					Werkstoffbezeichnung	Werkstoffnummer	Maßstab
					-	-	1,5:1
					Rohteil-/Vorteilnummer	Gewicht	
					-	0,5 kg	
		gepr.	22.11.22	AR	metal bellows coupling KG-VA 30 / 6W		
		gez.	18.11.22	IA			
Passung	Abmaß	Datum	Name	Benennung	Format	Artikelnummer	
DIN ISO 13715 -0,4 +0,8	DIN ISO 2768-mK 0,5 ... 6 ± 0,1 6 ... 30 ± 0,2 30 ... 120 ± 0,3 120 ... 315 ± 0,5 315 ... 1000 ± 0,8				A4	MB-133 24545 -e	
		D-63839-Kleinwallstadt		Ersatz für	-	ersetzt durch	-