



**technical data:**

nominal torque: 1000 Nm  
maximum torque: 2000 Nm  
torsional stiffness: 170 Nm/arcmin  
moment of inertia: 0,024 kgm<sup>2</sup>  
max. axial shaft displacement: ± 1 mm  
max. lateral shaft displacement: 0,3 mm  
axial spring rate: 120 N/mm  
lateral spring rate: 920 N/mm  
temperature range: -40° up to +350°C  
maximum speed: 7.000 rpm  
D1/2min/max = 54 / 90 mm

**material:**

bellows: stainless steel 1.4571 / A4  
hubs: stainless steel 1.4301 / A2  
clamping screws: stainless steel A4-80

Änderung					Werkstoffbezeichnung	Werkstoffnummer	Maßstab
					-	-	0,8
					Rohteil-/Vorteilnummer	Gewicht	
					-	ca.8,5 kg	
		gepr.	22.11.22	AR	metal bellows coupling		
		gez.	21.11.22	IA	KG-VA 1000 / 6W -standard		
Passung	Abmaß	gez.	Datum	Name	Benennung		
DIN ISO 13715	DIN ISO 2768-mK				Format A3	MB-133 24558 -e	
	0,5 ... 6 ± 0,1				Artikelnummer		
	6 ... 30 ± 0,2				Ersatz für	-	ersetzt durch -
	30 ... 120 ± 0,3						
	120 ... 315 ± 0,5						
	315 ... 1000 ± 0,8						