



Technical Data:
 setting range: 2 - 6 Nm
 torsional stiffness: 0,25 Nm/arcmin
 max. axial shaft displacement: $\pm 0,5$ mm
 max. lateral shaft displacement: 0,1 mm
 mass: approx. 0,44 kg
 moment of inertia: $0,13 \cdot 10^{-3} \text{ kgm}^2$
 $\phi D1$ min/max: 7 / 20 mm
 $\phi D2$ min/max: 6 / 16 mm
 temperature range: -30°C up to $+90^\circ\text{C}$

material
 safety part: heat-treated steel
 clamping hub: high-tensile strength aluminum
 elastomer spider: polyurethane - 98 Shore A
 screws: ISO 4762 / 12.9

		Änderung				Werkstoffbezeichnung	Werkstoffnummer	Maßstab
						-	-	
						Rohteil-/Vorteilnummer	Gewicht	1,5:1
						-	- kg	
		gepr.	17.08.23	IA	safety coupling SKB - EK 6			
Passung	Abmaß	gez.	24.05.17	Be				
DIN ISO 13715	DIN ISO 2768-mK	Datum	Name	Benennung				
	0,5 ... 6 ± 0,1 6 ... 30 ± 0,2 30 ... 120 ± 0,3 120 ... 315 ± 0,5 315 ... 1000 ± 0,8	 D-63839-Kleinwallstadt		Format A4 Artikelnummer MB - 142 17829-e				
				Ersatz für		-	ersetzt durch	-

safety coupling
SKB - EK 6

MB - 142 17829-e