


Flange Fasteners with SWAGELOK®, VCR & Ultra-Torr Screw Connections

Flange with SWAGELOK tube fitting for metric pipes

CF



DN	16	16	16	35	35
for pipe [mm]:	4	6	8	4	6
a mm	35	36	42	41	42,5
Øb mm	4	6	8	4	6
Swagelok® connection:	SS-4M0-1-2W	SS-6M0-1-2W	SS-8M0-1-4W	SS-4M0-1-2W	SS-6M0-1-2W
Art. Nr.:	33551989	33551755	33551990	33551991	33551992


according to DIN ISO 2768-mK

DN	35	35	35
für Rohr[mm]:	8	10	12
a mm	48	50,5	53
Øb mm	8	10	12
Swagelok® connection:	SS-8M0-1-4W	SS-10M0-1-6W	SS-12M0-1-6W
Art. Nr.:	33551993	33551994	33551995

- Other combinations on request
- Pressure range: $1 \cdot 10^{-9}$ hPa
- Material Flange: 1.4301
- Temperature range: -196°C up to 300°C

Flange with SWAGELOK tube fitting for inch pipes

CF



DN	16	16	16	35	35
a mm	34	41	43	40	47
Øb Zoll	1/8	1/4	3/8	1/8	1/4
Swagelok® connection:	SS-200-1-2W	SS-400-1-4W	SS-600-1-6W	SS-200-1-2W	SS-400-1-4W
Art. Nr.:	33551996	33551997	33551998	33551999	33552000

according to DIN ISO 2768-mK

DN	35	35	35
a mm	50	58,5	71,5
Øb Zoll	3/8	1/2	1
Swagelok® connection:	SS-600-1-6W	SS-810-1-8W	SS-1610-1-16W
Art. Nr.:	33552001	33552002	33552003

- Other combinations on request
- Pressure range: $1 \cdot 10^{-9}$ hPa
- Material flange: 1.4301
- Temperature range: -196°C up to 300°C