


Flexible Connectors

Flexible Connector with welded pipe ends




DN	16	35	63	100
Øa mm	18,2	38	70	104
b mm	15	28	38	57
c mm	15	28	38	57
d mm	72	116	127	194
e mm	27,5	50	82	133
Hub mm	± 8	± 10	± 8	± 13
Art.Nr.:	53651981	53651982	53651747	53651983
DN	150	200	250	
Øa mm	154	206	256	
b mm	67	70	75	
c mm	67	70	75	
d mm	214	265	260	
e mm	190	250	300	
Hub mm	± 11	± 15	± 15	
Art.Nr.:	53651984	53651985	53651986	

according to DIN ISO 2768-mK

- Other lengths on request
- Pressure range: $1 \cdot 10^{-10}$ hPa
- Temperature range: -196°C up to 300°C
- Material: Stainless steel 1.4571

Flexible Connector with 1 rotary flange and 1 fixed flange



DN	16	35	63	100
a mm	100	130	150	150
Øb mm	16	35	63	100
Øc mm	34	69,5	113,5	152
Hub mm	10	10	20	20
Art.Nr.:	33251959	33251960	33251753	33251961
DN	150	200	250	
a mm	180	250	250	
Øb mm	150	200	250	
Øc mm	202,5	253	306	
Hub mm	30	20	-	
Art.Nr.:	33251962	33251963	33251964	

according to DIN ISO 2768-mK

- Other lengths on request
- Flange with through hole
- Pressure range: $1 \cdot 10^{-10}$ hPa
- Temperature range: -196°C up to 300°C
- Material: Flange: Stainless steel 1.4301, bellows 1.4571