

Mechanical Power Clamping Screw I Series SC

Technical data and dimensions [mm]: length dimensions according to DIN ISO 2768 mH

SC Size	nominal clamping force [kN]	max. actuation torque [Nm]	max. clamping stroke [mm]	max. static load [kN]	operating path s [mm]	mass approx. [kg]	thread D* (6g)	Ø d	L1	L	SW 1	SW 2
36	50	30	1,5	80	5	0,5	M 36 x 3	19	62	73	13	30
48	100	70	2,2	160	7,5	1,1	M 48 x 3	28	75	90	17	41
64	150	120	2,5	250	8,5	2,5	M 64 x 4	39	90	110	19	55
80	200	140	2,5	300	8,5	5,3	M 80 x 4	39	100	160	19	65
100	250	130	3	400	17	12	TR 100 x 6	60	205	230	14**	65

*further sizes and threads (inch thread) available on request

allowed temperature range: -40°C up to +250°C

**hexagon socket - operating pin length: s = 17 mm

Note:

- to ensure the required clamping force is achieved and to protect the internal mechanism from damage, we recommend the use of a torque wrench for applying the actuation torque. Under certain conditions, clamping is also acceptable with a standard wrench or socket wrench.
- the clamping screws are lubricated for life and maintenance free under normal operating conditions. A high temperature version of up to 400°C is possible.

material:

heat treated steel - nitro carburized

Application example: slide-in-clamp

